

CE RoHS EASCO® 2 To 1 Single Wall Heat Shrink Tubing (2:1单壁热缩管)



Material: High quality PE

Shrinking ration: 2 to 1

Working Temperature: -55°C ~ +125°C

Rated Voltage: 600V

Using Method: Use with hot gun. Shrinkable.

Application: Providing full protection, insulation and cable identification.



Color available: Black, White, Red, Blue, Yellow, Green, Brown, Grey, Orange, Purple. Upon request.
材质: 采用优质照射交连PE化合物制成。适用温度-55°C-125°C, 额定使用电压600V。

使用方法: 使用热风枪加热即可收缩。

用途: 配线保护与识别、绝缘、包覆、端末处理、配线标字、分色等。

颜色: 黑、白、红、蓝、黄、绿、棕、灰、橙、紫。


Article No.	Part No.	I.D.	As Supplied 收缩前		After Shrinkage 收缩后		Flame Retardant	Pkg Qty (M/Reel)
货号	型号	内径	D	W	D1	W1	适用范围	包装 (米 / 盘)
A0113.000.0001	HST-0.6	Φ0.6	0.9±0.2	0.10±0.05	≤0.40	0.22±0.10	0.5-0.7	200
A0113.000.0002	HST-0.8	Φ0.8	1.0±0.2	0.15±0.05	≤0.50	0.22±0.10	0.6-0.8	200
A0113.000.0003	HST-1	Φ1.0	1.5±0.2	0.15±0.05	≤0.65	0.28±0.10	0.75-0.9	200
A0113.000.0004	HST-1.5	Φ1.5	2.0±0.2	0.15±0.05	≤0.85	0.28±0.10	0.95-1.4	200
A0113.000.0005	HST-2	Φ2.0	2.5±0.2	0.18±0.05	≤1.00	0.40±0.10	1.1-1.8	200
A0113.000.0006	HST-2.5	Φ2.5	3.0±0.2	0.18±0.05	≤1.30	0.40±0.10	1.4-2.3	200
A0113.000.0007	HST-3	Φ3.0	3.5±0.2	0.18±0.05	≤1.50	0.40±0.10	1.6-2.7	200
A0113.000.0008	HST-3.5	Φ3.5	4.0±0.2	0.22±0.05	≤1.80	0.42±0.10	1.9-3.2	200
A0113.000.0009	HST-4	Φ4.0	4.5±0.2	0.25±0.05	≤2.00	0.45±0.10	2.1-3.6	200
A0113.000.0010	HST-4.5	Φ4.5	5.0±0.2	0.25±0.05	≤2.30	0.50±0.10	2.4-4.0	100
A0113.000.0011	HST-5	Φ5.0	5.5±0.2	0.25±0.05	≤2.50	0.55±0.10	2.6-4.5	100
A0113.000.0012	HST-5.5	Φ5.5	6.0±0.2	0.25±0.05	≤2.75	0.55±0.10	2.8-5.0	100
A0113.000.0013	HST-6	Φ6.0	6.5±0.2	0.28±0.05	≤3.00	0.55±0.10	3.1-5.4	100
A0113.000.0014	HST-7	Φ7.0	7.5±0.3	0.28±0.05	≤3.50	0.55±0.10	3.7-6.3	100
A0113.000.0015	HST-8	Φ8.0	8.5±0.3	0.28±0.05	≤4.00	0.60±0.10	4.2-7.2	100
A0113.000.0016	HST-9	Φ9.0	9.5±0.3	0.30±0.08	≤4.50	0.60±0.10	4.7-8.0	100
A0113.000.0017	HST-10	Φ10	10.8±0.3	0.30±0.08	≤5.00	0.60±0.10	5.2-9.0	100
A0113.000.0018	HST-11	Φ11	11.5±0.3	0.30±0.08	≤5.50	0.60±0.10	5.7-10	100
A0113.000.0019	HST-12	Φ12	12.5±0.3	0.30±0.08	≤6.00	0.65±0.10	6.2-11	100
A0113.000.0020	HST-13	Φ13	13.5±0.3	0.35±0.10	≤6.50	0.65±0.10	6.7-12	100
A0113.000.0021	HST-14	Φ14	14.5±0.3	0.35±0.10	≤7.00	0.70±0.10	7.3-13	100
A0113.000.0022	HST-15	Φ15	15.5±0.4	0.40±0.12	≤7.50	0.75±0.10	7.8-14	100
A0113.000.0023	HST-16	Φ16	16.5±0.4	0.40±0.12	≤8.00	0.75±0.10	8.3-15	100
A0113.000.0024	HST-17	Φ17	17.5±0.4	0.40±0.12	≤8.50	0.75±0.10	8.8-16	100
A0113.000.0025	HST-18	Φ18	19.0±0.5	0.40±0.15	≤9.00	0.80±0.15	9.3-17	100
A0113.000.0026	HST-20	Φ20	22.0±0.5	0.40±0.15	≤10.00	0.82±0.15	10.4-19	100
A0113.000.0027	HST-22	Φ22	24.0±0.5	0.40±0.15	≤11.00	0.82±0.15	11.4-21	100
A0113.000.0028	HST-25	Φ25	26.0±0.5	0.55±0.15	≤12.50	1.00±0.15	12.8-24	50
A0113.000.0029	HST-28	Φ28	29.0±0.5	0.55±0.15	≤14.00	1.00±0.15	14.4-29	50
A0113.000.0030	HST-30	Φ30	31.5±1.0	0.55±0.15	≤15.00	1.05±0.15	16-29	50
A0113.000.0031	HST-35	Φ35	36.5±1.0	0.55±0.1	≤17.50	1.15±0.15	18-34	50
A0113.000.0032	HST-40	Φ40	41.5±1.0	0.55±0.15	≤20.00	1.20±0.15	21-39	50
A0113.000.0033	HST-50	Φ50	51.0±1.0	0.55±0.15	≤25.00	1.20±0.15	26-49	25
A0113.000.0034	HST-60	Φ60	60.0±1.0	0.60±0.15	≤31.00	1.30±0.20	35-55	25
A0113.000.0035	HST-70	Φ70	70.0±1.0	0.65±0.15	≤36.00	1.47±0.20	40-65	25
A0113.000.0036	HST-80	Φ80	80.0±1.0	0.65±0.15	≤41.00	1.47±0.20	45-75	25
A0113.000.0037	HST-90	Φ90	90.5±1.0	0.65±0.15	≤46.00	1.47±0.20	50-88	25
A0113.000.0038	HST-100	Φ100	100.5±1.0	0.65±0.20	≤51.00	1.47±0.20	55-95	25
A0113.000.0039	HST-120	Φ120	120.5±1.0	0.65±0.20	≤61.00	1.56±0.20	65-115	25
A0113.000.0040	HST-150	Φ150	150.5±1.0	0.65±0.20	≤76.00	1.56±0.20	80-145	25
A0113.000.0041	HST-180	Φ180	180.5±1.0	0.65±0.30	≤91.00	1.56±0.20	95-175	25



CE RoHS

EASCO® 2 To 1 Yellow Green Color Coded Heat Shrink Tubing

EASCO® 2:1单壁黄绿热缩管



Material: High quality PE

Shrinking ration: 2 to 1

Working Temperature: -55°C ~ +125°C

Rated Voltage: 600V

Using Method: Use with hot gun. Shrinkable.

Application: Providing full protection, insulation and cable identification for yellow and green color coded wiring applications.

Color available: Yellow & Green.


材质: 采用优质照射交连PE复合物制成。适用温度-55°C-125°C, 额定使用电压600V。

使用方法: 使用热风枪加热即可收缩。

用途: 主要用于黄绿电线的接头连接以及地线标识。

颜色: 黄绿条纹

Article No.	Part No.	I.D.	As Supplied 收缩前		After Shrinkage 收缩后		Flame Retardant	Pkg Qty (M/Reel)
货号	型号	内径	D	W	D1	W1	适用范围	包装 (米 / 盘)
A0113.002.0001	HST-1YG	Φ1.0	1.5±0.3	0.15±0.08	≤0.65	0.28±0.10	0.75-0.9	200
A0113.002.0002	HST-1.5YG	Φ1.5	2.0±0.3	0.15±0.08	≤0.65	0.28±0.10	0.75-0.9	200
A0113.002.0003	HST-2YG	Φ2.0	2.5±0.3	0.18±0.08	≤1.00	0.40±0.10	1.1-1.8	200
A0113.002.0004	HST-2.5YG	Φ2.5	3.0±0.3	0.18±0.08	≤1.30	0.40±0.10	1.35-2.3	200
A0113.002.0005	HST-3YG	Φ3.0	3.5±0.4	0.18±0.08	≤1.50	0.40±0.10	1.6-2.7	200
A0113.002.0006	HST-3.5 YG	Φ3.5	4.0±0.4	0.22±0.08	≤1.80	0.42±0.10	1.85-3.2	200
A0113.002.0007	HST-4YG	Φ4.0	4.5±0.4	0.25±0.08	≤2.00	0.45±0.10	2.1-3.6	200
A0113.002.0008	HST-4.5YG	Φ4.5	5.0±0.4	0.25±0.08	≤2.30	0.50±0.10	2.35-4.0	100
A0113.002.0009	HST-5YG	Φ5.0	5.5±0.4	0.25±0.08	≤2.50	0.55±0.10	2.6-4.5	100
A0113.002.0010	HST-6YG	Φ6.0	6.5±0.4	0.28±0.08	≤3.00	0.55±0.10	3.1-5.4	100
A0113.002.0011	HST-7YG	Φ7.0	7.5±0.4	0.28±0.08	≤3.50	0.55±0.10	3.7-6.3	100
A0113.002.0012	HST-8YG	Φ8.0	8.5±0.5	0.28±0.08	≤4.00	0.60±0.10	4.2-7.2	100
A0113.002.0013	HST-9YG	Φ9.0	9.5±0.5	0.30±0.10	≤4.50	0.60±0.10	4.7-8.0	100
A0113.002.0014	HST-10YG	Φ10	10.8±0.5	0.30±0.10	≤5.00	0.60±0.10	5.2-9.0	100
A0113.002.0015	HST-11YG	Φ11	11.5±0.5	0.30±0.10	≤5.50	0.60±0.10	5.7-10	100
A0113.002.0016	HST-12YG	Φ12	12.5±0.5	0.30±0.10	≤6.00	0.65±0.10	6.2-11	100
A0113.002.0017	HST-13YG	Φ13	13.5±0.5	0.35±0.12	≤6.50	0.65±0.10	6.7-12	100
A0113.002.0018	HST-14YG	Φ14	14.5±0.5	0.35±0.12	≤7.00	0.70±0.10	7.3-13	100
A0113.002.0019	HST-15YG	Φ15	15.5±0.6	0.40±0.12	≤7.50	0.75±0.10	7.8-14	100
A0113.002.0020	HST-16YG	Φ16	16.5±0.6	0.40±0.12	≤8.00	0.75±0.10	8.3-15	100
A0113.002.0021	HST-17YG	Φ17	17.5±0.6	0.40±0.12	≤8.50	0.75±0.10	8.8-16	100
A0113.002.0022	HST-18YG	Φ18	19.0±0.7	0.40±0.15	≤9.00	0.80±0.15	9.3-17	100
A0113.002.0023	HST-20YG	Φ20	22.0±0.7 0	0.40±0.15	≤10.00	0.82±0.15	10.4-19	100
A0113.002.0024	HST-22YG	Φ22	24.0±0.7	0.40±0.15	≤11.00	0.82±0.15	11.4-21	100
A0113.002.0025	HST-25YG	Φ25	26.0±0.7	0.55±0.15	≤12.50	1.00±0.15	12.8-24	50
A0113.002.0026	HST-28YG	Φ28	29.0±0.7	0.55±0.15	≤14.00	1.00±0.15	14.4-29	50
A0113.002.0027	HST-30YG	Φ30	31.5±0.7	0.55±0.15	≤15.00	1.05±0.15	16-29	50
A0113.002.0028	HST-35YG	Φ35	36.5±0.7	0.55±0.1	≤17.50	1.15±0.15	18-34	50
A0113.002.0029	HST-40YG	Φ40	41.5±0.7	0.55±0.15	≤20.00	1.20±0.15	21-39	50
A0113.002.0030	HST-50YG	Φ50	51.0±0.7	0.55±0.15	≤25.00	1.20±0.15	26-49	25
A0113.002.0031	HST-60YG	Φ60	60.0±0.8	0.60±0.15	≤31.00	1.50±0.20	35-55	25
A0113.002.0032	HST-70YG	Φ70	70.0±0.8	0.65±0.15	≤36.00	1.60±0.20	40-65	25
A0113.002.0033	HST-80YG	Φ80	80.0±0.8	0.70±0.15	≤41.00	1.70±0.20	45-75	25
A0113.002.0034	HST-90YG	Φ90	90.5±0.8	0.70±0.15	≤46.00	1.90±0.20	50-88	25
A0113.002.0035	HST-100YG	Φ100	100.5±0.8	0.70±0.20	≤51.00	2.10±0.20	55-95	25
A0113.002.0036	HST-120YG	Φ120	120.5±0.8	0.70±0.20	≤61.00	2.30±0.20	65-115	15
A0113.002.0037	HST-150YG	Φ150	150.5±0.8	0.70±0.20	≤76.00	2.30±0.20	80-145	15
A0113.002.0038	HST-180YG	Φ180	180.5±0.8	0.70±0.20	≤91.00	2.30±0.20	95-175	15



A1.
Wiring
Ducts

A2.
Cable
Ties

A3.
Din
Rails

A4.
Cable
Markers

A5.
Cable
Clamps

A6.
Wrapping
Bands

A7.
Nylon
Cable Gland

A8.
Metal
Cable Gland

A9.
Plastic
Flexible
Conduit

A10.
Metal
Flexible
Conduit

A11.
Terminal

A12.
Copper
Tube
Terminals

A13.
Heat
Shrinkable
Tubings

A14.
Bus Bar
Insulators


A15.
Tool

A16.
Cable
Clip

A17.
Insulating
Nut


A18.
Nylon Cable
Carrier

CE RoHS EASCO® 3 To 1 Dual Wall Heat Shrink Tubing (3:1双壁热缩管)




Material: High quality PE
Shrinking ration: 3 to 1
Working Temperature: -55°C ~ +125°C
Rated Voltage: 600V
Using Method: Use with hot gun. Shrinkable.
Application: Providing full protection, insulation and cable identification.
Color available: Black, White, Red, Blue, Yellow, Green, Brown, Grey, Orange, Purple. Upon request.
材质: 采用优质照射交连PE复合物制成。适用温度-55°C-125°C, 额定使用电压600V。
使用方法: 使用热风枪加热即可收缩。
用途: 配线保护与识别、绝缘、包覆、端末处理、配线标字、分色等。
颜色: 黑、白、红、蓝、黄、绿、棕、灰、橙、紫。

Article No.	Part No.	I.D.	As Supplied 收缩前		After Shrinkage 收缩后		Flame Retardant	Pkg Qty (M/Reel)
货号	型号	内径	D	W	D1	W1	适用范围	包装 (米 / 盘)
A0113.003.0001	SCM-01	1/8	3.2±0.6	0.30±0.08	≤1.0	0.95±0.08	1.0~3.1	200
A0113.003.0002	SCM-02	3/16	4.8±0.6	0.46±0.08	≤1.6	1.10±0.08	1.8~4.6	100
A0113.003.0003	SCM-03S	1/4	6.4±0.6	0.50±0.08	≤2.2	1.20±0.08	2.4~6.4	100
A0113.003.0004	SCM-03L	5/16	7.9±0.6	0.52±0.08	≤2.7	1.30±0.08	2.9~7.7	100
A0113.003.0005	SCM-04	3/8	9.5±0.6	0.55±0.08	≤3.2	1.40±0.08	3.4~9.4	50
A0113.003.0006	SCM-05	1/2	12.7±0.6	0.68±0.08	≤4.2	1.50±1.0	4.4~12.5	1.22M/PCS 1.22 米 / 支
A0113.003.0007	SCM-06	5/8	15.0±0.6	0.71±0.10	≤5.2	1.80±1.0	5.4~14.8	
A0113.003.0008	SCM-07	3/4	19.0±0.8	0.76±0.10	≤6.3	2.00±1.0	6.5~18.8	
A0113.003.0009	SCM-11	1	25.4±0.8	0.78±0.10	≤8.5	2.10±1.0	8.8~25	
A0113.003.0010	SCM-13	1 1/4	30.0±0.8	0.80±0.10	≤10.2	2.20±1.0	11~30	
A0113.003.0011	SCM-15	1 1/2	≥39	0.85±0.10	≤13.5	2.40±1.0	14~40	
A0113.003.0012	SCM-17	2	≥50	0.95±0.10	≤17.0	2.80±1.0	14~44	
A0113.003.0013	SCM-20	2	≥52	0.95±0.10	≤17.0	3.00±1.0	18~49	
A0113.003.0014	SCM-23	2 1/2	≥64	0.95±0.10	≤21.0	3.00±0.15	22~62	
A0113.003.0015	SCM-27	3	≥76	1.00±0.15	≤25.0	3.20±0.15	26~75	
A0113.003.0016	SCM-35	3 1/2	≥90	1.00±0.15	≤30.0	3.30±0.15	32~88	
A0113.003.0017	SCM-40	4	≥100	1.20±0.1	≤34.0	3.50±0.15	36~99	
A0113.003.0018	SCM-50	5	≥125	1.20±0.15	≤42.0	3.50±0.15	44~125	




CE RoHS EASCO® 4 To 1 Dual Wall Heat Shrink Tubing (4:1双壁热缩管)



Material: High quality PE
Shrinking ration: 4 to 1
Working Temperature: -55°C ~ +125°C
Rated Voltage: 600V
Using Method: Use with hot gun. Shrinkable.
Application: Providing full protection, insulation and cable identification.
Color available: Black, White, Red, Blue, Yellow, Green, Brown, Grey, Orange, Purple. Upon request.
材质: 采用优质照射交连PE复合物制成。适用温度-55°C-125°C, 额定使用电压600V。
使用方法: 使用热风枪加热即可收缩。
用途: 配线保护与识别、绝缘、包覆、端末处理、配线标字、分色等。
颜色: 黑、白、红、蓝、黄、绿、棕、灰、橙、紫。

Article No.	Part No.	I.D.	As Supplied 收缩前		After Shrinkage 收缩后		Flame Retardant	Pkg Qty (M/Reel)
货号	型号	内径	D	W	D1	W1	适用范围	包装 (米 / 盘)
A0113.004.0001	SCM6-1.2	Φ6	6±0.08	1.27	1.30±0.15	0.56±0.15	1.27-6	1.22M/PCS 1.22 米 / 支
A0113.004.0002	SCM8-1.6	Φ8	8±0.08	1.65	1.65±0.15	0.76±0.15	1.65-8	
A0113.004.0003	SCM12-2.4	Φ12	12±0.08	2.41	2.00±0.15	1.02±0.15	2.41-12	
A0113.004.0004	SCM18-4.4	Φ18	18±0.08	4.45	2.50±0.15	1.37±0.15	4.45-18	




CE RoHS EASCO® 1KV Busbar Heat Shrink Tubing (1KV铜排热缩管)



Material: High quality PE.
 Shrinking ration: 2 to 1
 With or without glue: Without glue inside.
 Working Temperature: -40°C ~ +125°C
 Shrinking temperature: +70°C
 Fully shrinking temperature: +125°C
 Color available: Red, Yellow, Green. Special color is available upon reasonable request such as Black, Blue.
 Application: Providing full protection, insulation and avoid short circuit for high volatage.
 材质: 采用优质照射交连PE复合物制成。
 特性: 适合高压保护用。
 温度: 起始收缩温度70°C, 全部收缩温度125°C; 适用温度-40°C-125°C, 可在酸碱条件下长期使用。
 颜色: 红色、黄色、绿色, 其他颜色如: 黑色、蓝色等可定做。
 用途: 用于变电站, 高低压开关柜等母排绝缘保护, 防止短路。

Article No.	Part No.	Busbar Width (Square)	As Supplied (D)	After Shrinkage (D1)	Wall Thickness (W)	Pkg Qty (M/Reel)
货号	型号	母排宽度 (方排)	收缩前 (D)	收缩后 (D1)	壁厚 (W)	包装 (米 / 盘)
A0113.006.0001	1KVSBI-30/15	30	31.5	15.0	0.95	50
A0113.006.0002	1KVSBI-35/18	35	36.5	18.0	1.00	50
A0113.006.0003	1KVSBI-40/20	40	41.5	20.0	1.00	50
A0113.006.0004	1KVSBI-45/23	45	46.5	23.0	1.00	25
A0113.006.0005	1KVSBI-50/25	50	51	25.0	1.00	25
A0113.006.0006	1KVSBI-60/30	60	60	30.0	1.30	25
A0113.006.0007	1KVSBI-65/33*	65	65	33.0	1.30	25
A0113.006.0008	1KVSBI-70/35	70	70	35.0	1.30	25
A0113.006.0009	1KVSBI-75/38*	75	75	38.0	1.30	25
A0113.006.0010	1KVSBI-80/40	80/100	80	40.0	1.46	25
A0113.006.0011	1KVSBI-85/43*	80/100	85	43.0	1.46	25
A0113.006.0012	1KVSBI-90/45	100	90	45.0	1.46	25
A0113.006.0013	1KVSBI-100/50	100/120	100	50.0	1.46	25
A0113.006.0014	1KVSBI-120/60	150	120	60.0	1.46	25
A0113.006.0015	1KVSBI-150/75	180	150	75.0	1.46	25
A0113.006.0016	1KVSBI-180/90	MAX	180	90.0	1.46	25
A0113.006.0017	1KVSBI-210/105*	MAX	210	105	1.46	25
A0113.006.0018	1KVSBI-230/115*	MAX	230	115	1.46	25
A0113.006.0019	1KVSBI-250/125*	MAX	250	125	1.46	25
A0113.006.0020	1KVSBI-300/150*	MAX	300	150	1.46	25



CE RoHS EASCO® 10KV Busbar Heat Shrink Tubing (10KV铜排热缩管)



Material: High quality PE.

Shrinking ration: 2 to 1

With or without glue: Without glue inside.

Working Temperature: -40°C ~ +125°C

Shrinking temperature: +70°C

Fully shrinking temperature: +125°C

Color available: Red, Yellow, Green. Special color is available upon reasonable request such as Black, Blue.

Application: Providing full protection, insulation and avoid short circuit for high volatage.

材质: 采用优质照射交连PE复合物制成。



特性: 适合高压保护用。

温度: 起始收缩温度70°C, 全部收缩温度125°C; 适用温度-40°C-125°C, 可在酸碱条件下长期使用。

颜色: 红色、黄色、绿色, 其他颜色如: 黑色、蓝色等可定做。

用途: 用于变电站, 高低压开关柜等母排绝缘保护, 防止短路。

Article No.	Part No.	Busbar Width 母排宽度		As Supplied (D)	After Shrinkage (D1)	Wall Thickness (W)	Pkg Qty (M/Reel)
货号	型号	Square Busbar 方形母排	Round Busbar 圆形母排	收缩前 (D)	收缩后 (D1)	壁厚 (W)	包装 (米 / 盘)
A0113.007.0001	10KVSBI-15/8	12	12	15	8.0	2.10	25
A0113.007.0002	10KVSBI-20/10	20	15	20	10.0	2.10	25
A0113.007.0003	10KVSBI-25/13	25	18	25	12.5	2.10	25
A0113.007.0004	10KVSBI-30/15	30	20	30	15.0	2.10	25
A0113.007.0005	10KVSBI-40/20	40	30	40	20.0	2.30	25
A0113.007.0006	10KVSBI-50/25	50	35	50	25.0	2.30	25
A0113.007.0007	10KVSBI-60/30	60	45	60	30.0	2.30	25
A0113.007.0008	10KVSBI-65/33*	65	45	65	33.0	2.30	25
A0113.007.0009	10KVSBI-70/35	70	50	70	35.0	2.30	25
A0113.007.0010	10KVSBI-75/38*	75	50	75	38.0	2.30	25
A0113.007.0011	10KVSBI-80/40	80	55	80	40.0	2.30	25
A0113.007.0012	10KVSBI-85/43*	80	65	85	43.0	2.30	25
A0113.007.0013	10KVSBI-100/50	100	75	100	50.0	2.30	25
A0113.007.0014	10KVSBI-120/60	120	85	120	60.0	2.30	25
A0113.007.0015	10KVSBI-150/75	150	105	150	75.0	2.30	25
A0113.007.0016	10KVSBI-180/90	180	120	180	90.0	2.30	25
A0113.007.0017	10KVSBI-210/105*	210	140	210	105	2.30	20
A0113.007.0018	10KVSBI-230/115*	230	150	230	115	2.30	20
A0113.007.0019	10KVSBI-250/125*	250	180	250	125	2.30	20
A0113.007.0020	10KVSBI-300/150*	300	210	300	150	2.30	15




CE RoHS EASCO® 20KV Busbar Heat Shrink Tubing (20KV铜排热缩管)



Material: High quality PE.
 Shrinking ration: 2 to 1
 With or without glue: Without glue inside.
 Working Temperature: -40°C ~ +125°C
 Shrinking temperature: +70°C
 Fully shrinking temperature: +125°C
 Color available: Red, Yellow, Green. Special color is available upon reasonable request such as Black, Blue.
 Application: Providing full protection, insulation and avoid short circuit for high volatage.
 材质: 采用优质照射交连PE复合物制成。
 特性: 适合高压保护用。
 温度: 起始收缩温度70°C, 全部收缩温度125°C; 适用温度-40°C-125°C, 可在酸碱条件下长期使用。
 颜色: 红色、黄色、绿色, 其他颜色如: 黑色、蓝色等可定做。
 用途: 用于变电站, 高低压开关柜等母排绝缘保护, 防止短路。

Article No.	Part No.	Busbar Width 母排宽度		As Supplied (D)	After Shrinkage (D1)	Wall Thickness (W)	Pkg Qty (M/Reel)
货号	型号	Square Busbar 方形母排	Round Busbar 圆形母排	收缩前 (D)	收缩后 (D1)	壁厚 (W)	包装 (米 / 盘)
A0113.008.0001	20KVSBI-15/8	15	12	15	8.0	2.50	25
A0113.008.0002	20KVSBI-20/10	20	15	20	10.0	2.50	25
A0113.008.0003	20KVSBI-25/13	25	18	25	13.0	2.50	25
A0113.008.0004	20KVSBI-30/15	30	20	30	15.0	2.50	25
A0113.008.0005	20KVSBI-40/20	40	30	40	20.0	2.80	25
A0113.008.0006	20KVSBI-50/25	50	35	50	25.0	2.80	25
A0113.008.0007	20KVSBI-60/30	60	45	60	30.0	2.80	25
A0113.008.0008	20KVSBI-65/33*	65	45	65	33.0	2.80	25
A0113.008.0009	20KVSBI-70/35	70	50	70	35.0	2.80	25
A0113.008.0010	20KVSBI-75/38	75	50	75	38.0	2.80	25
A0113.008.0011	20KVSBI-80/40	80	55	80	40.0	2.80	25
A0113.008.0012	20KVSBI-85/43*	80	65	85	43.0	2.80	25
A0113.008.0013	20KVSBI-100/50	100	75	100	50.0	2.80	25
A0113.008.0014	20KVSBI-120/60	120	85	120	60.0	2.80	25
A0113.008.0015	20KVSBI-150/75	150	105	150	75.0	2.80	25
A0113.008.0016	20KVSBI-180/90	180	120	180	90.0	2.80	25
A0113.008.0017	20KVSBI-210/105*	210	140	210	105	2.80	20
A0113.008.0018	20KVSBI-230/115*	230	150	230	115	2.80	20



CE RoHS EASCO® 35KV Busbar Heat Shrink Tubing (35KV铜排热缩管)



Material: High quality PE.

Shrinking ration: 2 to 1

With or without glue: Without glue inside.

Working Temperature: -40°C ~ +125°C

Shrinking temperature: +70°C

Fully shrinking temperature: +125°C

Color available: Red, Yellow, Green. Special color is available upon reasonable request such as Black, Blue.

Application: Providing full protection, insulation and avoid short circuit for high volatage.

材质: 采用优质照射交连PE复合物制成。

特性: 适合高压保护用。

温度: 起始收缩温度70°C, 全部收缩温度125°C; 适用温度-40°C-125°C, 可在酸碱条件下长期使用。

颜色: 红色、黄色、绿色, 其他颜色如: 黑色、蓝色等可定做。

用途: 用于变电站, 高低压开关柜等母排绝缘保护, 防止短路。

Article No.	Part No.	Busbar Width (Square)	As Supplied (D)	After Shrinkage (D1)	Wall Thickness (W)	Pkg Qty (M/Reel)
货号	型号	母排宽度 (方排)	收缩前 (D)	收缩后 (D1)	壁厚 (W)	包装 (米 / 盘)
A0113.009.0001	35KVSBI-15/8	15/12	15	8.0	4.00	15
A0113.009.0002	35KVSBI-20/10	20/15	20	10.0	4.00	15
A0113.009.0003	35KVSBI-30/15	30	30	15.0	4.00	15
A0113.009.0004	35KVSBI-35/18	30/40	35	18.0	4.00	15
A0113.009.0005	35KVSBI-40/20	40	40	20.0	4.00	15
A0113.009.0006	35KVSBI-50/25	50	50	25.0	4.00	15
A0113.009.0007	35KVSBI-60/30	60	60	30.0	4.00	15
A0113.009.0008	35KVSBI-65/33*	60/70	65	33.0	4.00	15
A0113.009.0009	35KVSBI-70/35	70	70	35.0	4.00	15
A0113.009.0010	35KVSBI-75/38*	70/80	75	38.0	4.00	15
A0113.009.0011	35KVSBI-80/40	80/100	80	40.0	4.00	15
A0113.009.0012	35KVSBI-100/50	100/120	100	50.0	4.00	15
A0113.009.0013	35KVSBI-120/60	150	120	60.0	4.00	15
A0113.009.0014	35KVSBI-150/75	180	150	75.0	4.00	15
A0113.009.0015	35KVSBI-180/90*	MAX.	180	90.0	4.00	15
A0113.009.0016	35KVSBI-210/105*	MAX.	210	105	4.00	15
A0113.009.0017	35KVSBI-230/115*	MAX.	230	115	4.00	15
A0113.009.0018	35KVSBI-250/125*	MAX.	250	125	4.00	15
A0113.009.0019	35KVSBI-300/150*	MAX.	300	150	4.00	15

